

# ATX720

## COMPACT ARTICULATED LOADER



### GENERAL DIMENSIONS

Length: 109.8 in (278.9 cm)

Width: 44.5 in (113 cm)

Height: 79.5 in (201.9 cm)

Weight (with rear weights and no attachments): 3,902 lb (1,770 kg)

Ground clearance: 8.3 in (21.1 cm)

Angle of departure with rear weights: 19°

### ENGINE

Make/Model: Kubota D1305 Tier 4 Final

Fuel type: Diesel

Fuel tank capacity: 9 gal (34 L)

Gross horsepower: 25 hp (18.6 kW)

Cooling system: Liquid

Transmission: Hydrostatic

### PERFORMANCE

Rated operating capacity (straight): 2,155 lb (978 kg)

Rated operating capacity (articulated): 1,658 lb (752 kg)

Tipping capacity (straight): 2,694 lb (1,222 kg)

Tipping capacity (articulated): 2,072 lb (940 kg)

Travel speed: 5.6 mph (9 km/hr)

Turning radius (inside/outside): 32.5 in - 82.3 in (82.6 cm - 209 cm)

Standard tires: 23x10.50-12

Pivot point height (extended boom): 114 in (289.6 cm)

Outreach with horizontal boom (extended boom): 46.6 in (118.4 cm)

\*Operating capacities shown have the boom low to the ground, boom not extended and the rear counterweights installed. The rating shown is for a fork attachment at 80% of the tipping load per EN 474-3:2006+A1:2019.

### HYDRAULIC SYSTEM

Auxiliary hydraulics oil flow: 9.8 gpm (37.1 L/min)

Hydraulic oil tank capacity: 11.1 gal (42 L)

MultiOne SRL Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components specific to their global region. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer and the Vermeer logo are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Kubota is a trademark of Kubota Engine Corporation. © 2021 Vermeer Corporation. All Rights Reserved.